



AMERICA OIL – CODE 220

Description: A white helix embedded in blue oil resistant superelastic flexible pvc compound.

Temperature: - 20°C +55°C.

Application: This hose is suitable for the medium duty suction and discharge of black fuel oils, gas oils, kerosene, paraffin, hydraulic oils, mineral based oils, lubricating oils and greases. It is not suitable for benzene, xylol and aromatic solvents.

Advantages: Although designed for medium duty applications this hose remains very flexible and is easy to handle in use.



I.D. ins.	Wall Thickness mm.	Weight gr./mtr.	Bending Radius mm.	Vacuum m.H2O	Working Pressure bar	Coil Length mtr.
3/4	2.8	450	90	7	6	30
1	3	500	90	7	6	30
1 1/4	4.5	600	110	7	5	30
1 1/2	4.7	700	130	7	5	30
2	5.5	1050	175	7	4.5	30
2 1/2	6	1390	220	7	4	30
3	6.4	1700	270	7	3.5	30
4	7.4	2700	360	7	2.5	30

**All data refers to performance at 18°C. Any increase of temperature, above or below, will affect the performance data. We reserve the right to change all technical data without prior notice.

BRANCHES AT:

2 Witney Road
Nuffield Industrial Estate

POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

poole@hyphose.com

Unit 3, The Warrior Centre
Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

portsmouth@hyphose.com

Unit 1, Trinity Industrial Estate
Millbrook Road

SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

southampton@hyphose.com

www.hyphose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK