



ARIZONA™ SUPERELASTIC - CODE 170



Description: A white spiral helix embedded in a grey superelastic flexible PVC.

The hose has a patented and distinctive green external spiral scuff strip.

Temperature Range: -25°C +55°C.

Applications: A cesspit and gully emptying hose, waste water hose, widely used in agriculture as tanker slurry hose, injector hose, irrigator, used as grain animal feed hose.

Advantages: Very easy to handle, performs very well at low temperature.

Excellent weathering resistance.

Good crush and scuff resistance.

BRANCHES AT:

2 Witney Road

Nuffield Industrial Estate

POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

poole@hyphose.com

Unit 3, The Warrior Centre

Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

portsmouth@hyphose.com

Unit 1, Trinity Industrial Estate

Millbrook Road

SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

southampton@hyphose.com

www.hyphose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK

ARIZONA™ SUPERELASTIC - CODE 170

I.D. inch	I.D. mm.	Wall Thickness mm.	Weight gr./mtr.	Bending Radius mm.	Vacuum m.H2O	Working Pressure bar	Bursting Pressure bar	Coil Length mtr.
1	25	4.4	500	100	9	7.0	21	30
1 1/4	32	4.4	600	130	9	6.0	18	30
1 1/2	38	4.4	700	150	9	6.0	18	30
1 3/4	45	5	900	180	9	5.5	16.5	50
2	50	5.5	1050	200	9	5.0	15	30
.	60	5.6	1250	240	9	4.5	13.5	30
2 1/2	63	5.5	1390	250	9	4.5	13.5	30
.	75	6.5	1700	300	9	4.0	12	30
3	76	6.5	1700	300	9	4.0	12	30
.	80	6.5	1850	320	9	3.5	10.5	30
3 1/2	89	6.7	2250	360	9	3.5	10.5	30
.	90	6.7	2250	360	9	3.5	10.5	30
.	100	7.4	2700	400	9	3.0	9.0	30
4	102	7.3	2700	400	9	3.0	9.0	30
.	110	7.5	3100	440	9	3.0	9.0	30
.	120	7.8	3600	480	9	2.5	7.5	20
.	125	8.3	3900	500	9	2.5	7.5	20
5	127	8.3	3900	510	9	2.5	7.5	30
.	130	8.5	4100	520	9	2.5	7.5	20
.	133	8.5	4200	550	9	2.0	7.0	20
.	150	9	5000	600	9	3.2	6.0	20
6	152	9	5000	610	9	2.0	6.0	20
.	160	9.4	5600	640	9	2.0	6.0	20
8	203	13	10000	800	9	1.5	4.5	10
10	250	15	14000	1000	7	1.5	4.5	10

Available in straight cured lengths 3in, 4in, 8in - 6mtr.
6in - 4.57mtr. and 6 mtr.

**All data refers to performance at 18°C. Any increase of temperature, above or below, will affect the performance data.
We reserve the right to change all technical data without prior notice.

BRANCHES AT:

2 Witney Road
Nuffield Industrial Estate

POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

poole@hyphose.com

Unit 3, The Warrior Centre
Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

portsmouth@hyphose.com

Unit 1, Trinity Industrial Estate
Millbrook Road

SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

southampton@hyphose.com

www.hyphose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK