



ARIZONA™ PU - CODE 177

Description: A white spiral helix embedded in a thick grey superelastic flexible PVC with a polyurethane liner. The helix is covered with polyurethane.

Temperature Range: -25°C +55°C

Applications: A hose where a high degree of abrasion resistance is required for both inner tube and external cover. This hose has an excellent abrasion resistance to cereals, grains, animal feeds, sand and gravel.

It is also suitable for slurries and large particle transfer in dry or liquid form.

Advantages: A hose for aggressive applications and providing longer life than conventional PVC hoses yet remaining lightweight and easy to handle.



I.D. inch	I.D. mm.	Wall Thickness mm.	Weight gr./mtr.	Bending Radius mm.	Vacuum m.H2O	Working Pressure bar	Cover Thickness PU mm.	Coil Length mtr.
1 1/4	32	4.4	600	130	7	6	0.8	50
1 1/2	38	4.4	700	150	7	6	0.8	50
1 3/4	45	5	900	180	7	5.5	0.8	50
2	50	5.5	1050	200	7	5	0.9	50
2 1/2	63	5.5	1390	250	7	4.5	0.9	50
3	76	6.5	1700	300	7	4	0.9	30
3 1/2	89	6.7	2250	360	7	3.5	1.0	30
4	102	7.3	2700	400	7	3	1.1	30
5	127	8.3	3900	510	7	2.5	1.2	20
6	152	9	5000	610	7	2	1.2	20

**All data refers to performance at 18°C. Any increase of temperature, above or below, will affect the performance data. We reserve the right to change all technical data without prior notice.

BRANCHES AT:

2 Witney Road
Nuffield Industrial Estate

POOLE

BH17 0GH
Tel: 01202 673333
Fax: 01202 687788

poole@hypohose.com

Unit 3, The Warrior Centre
Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX
Tel: 023 92 324644
Fax: 023 92 325549

portsmouth@hypohose.com

Unit 1, Trinity Industrial Estate
Millbrook Road

SOUTHAMPTON

SO15 0LA
Tel: 023 80 512555
Fax: 023 80 512999

southampton@hypohose.com

www.hypohose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK