




ARIZONA™ GREEN MEDIUM - CODE 180

Description: A white spiral helix embedded in an opaque green flexible PVC.

Temperature Range: -25°C +55°C

Applications: A cesspit and gully emptying hose, waste water hose, widely used in agriculture as tanker slurry hose, or hose, irrigator, used as grain animal feed hose. Suitable for dilute chemicals.

Advantages: Very easy to handle.
Excellent weathering resistance.
Good crush resistance.
A robust general purpose hose.



I.D. inch.	I.D. mm.	Weight gr./mtr.	Bending Radius mm.	Bursting Pressure bar	Vacuum m.H2O	Coil Length mtr.
1	25	340	110	21	7	30
1 1/4	32	460	135	18	7	30
1 1/2	38	550	150	15	7	30
2	51	960	200	13.5	9	30
2 1/2	63	1300	250	12	9	30
3	76	1700	300	10.5	9	30
4	102	2600	400	9	9	30
5	127	3600	510	6.9	9	30
6	152	4700	610	5.4	9	20/30

**All data refers to performance at 18°C. Any increase of temperature, above or below, will affect the performance data.
We reserve the right to change all technical data without prior notice.

BRANCHES AT:

2 Witney Road
Nuffield Industrial Estate

POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

poole@hyphose.com

Unit 3, The Warrior Centre
Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

portsmouth@hyphose.com

Unit 1, Trinity Industrial Estate
Millbrook Road

SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

southampton@hyphose.com

www.hyphose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK