



FLEXITEX EXTRA IRRIGATION LAYFLAT - CODE 750

Description: This hose is produced in a continuous process where Nitrile rubber is forced through a circular woven textile.

Temperature: -30°C +70°C.

Application: Agriculture, industry, construction and water authorities. This layflat is used for irrigation of sludge and slurry where the hose is being used as a transfer hose or a drag hose.

Advantages: Highly resistant to oil and other chemicals. Lightweight and pliable. Requires less space in storage and can be delivered in lengths of up to 200 metres. High working and burst pressures.



I.D. inches.	I.D. mm.	Wall Thickness mm.	Weight gr./mtr.	Bursting Pressure bar	Coil Length mtr.
2	51	2.8	500	60	200
2 1/2	65	2.9	700	50	200
3	76	3.0	900	50	200
3 1/2	90	3.3	1000	40	200
4	102	3.3	1350	35	200
4 1/2	114	3.3	1400	35	200
5	127	3.3	1650	30	200
6	150	3.4	1900	30	200

**All data refers to performance at 18°C.

Any increase of temperature, above or below, will affect the performance data.

We reserve the right to change all technical data without prior notice.

BRANCHES AT:

2 Witney Road

Nuffield Industrial Estate

POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

poole@hyphose.com

Unit 3, The Warrior Centre

Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

portsmouth@hyphose.com

Unit 1, Trinity Industrial Estate

Millbrook Road

SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

southampton@hyphose.com

www.hyphose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK