



## FLEXITEX STANDARD IRRIGATION LAYFLAT - CODE 751

**Description:** This hose is produced in a continuous process where Nitrile rubber is forced through a circular woven textile.

**Temperature:** -30°C +70°C.

**Application:** Agriculture, industry, construction and water authorities. This layflat is used for irrigation of sludge and slurry where the hose is being used as a transfer hose. Also can be used as an air hose.

**Advantages:** Highly resistant to oil and other chemicals. Lightweight and pliable. Requires less space in storage and can be delivered in lengths of up to 200 metres. High working and burst pressures.



I.D. inches.	I.D. mm.	Wall Thickness mm.	Weight gr./mtr.	Bursting Pressure bar	Coil Length mtr.
3/4	20	2.3	180	70	200
1	25	2.5	240	70	200
1 1/2	38	2.2	300	50	200
2	51	2.2	350	45	200
2 1/2	65	2.6	500	45	200
3	76	2.6	650	40	200
4	102	2.7	1000	30	200
6	150	2.9	1600	30	200

\*\*All data refers to performance at 18°C.

Any increase of temperature, above or below, will affect the performance data.

We reserve the right to change all technical data without prior notice.

### BRANCHES AT:

2 Witney Road  
Nuffield Industrial Estate

#### POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

[poole@hyphose.com](mailto:poole@hyphose.com)

Unit 3, The Warrior Centre  
Fitzherbert Road, Farlington

#### PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

[portsmouth@hyphose.com](mailto:portsmouth@hyphose.com)

Unit 1, Trinity Industrial Estate  
Millbrook Road

#### SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

[southampton@hyphose.com](mailto:southampton@hyphose.com)

[www.hyphose.com](http://www.hyphose.com)

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK