



GAS HOSE - OXYGEN/ACETYLENE

Rubber hose manufactured to EN559

Cover: Smooth (/L) or ribbed (/R), red (NR) or blue (NB), SBR/EPDM rubber compound resistant to abrasion, ageing, hot surfaces and incandescent particles.

Branding: Rubber Hose / EN559 / 2 Mpa (20 bar) / I.D. made in Italy / Parker ITR (year with traceability code)

Reinforcement: Synthetic textile yarns.

Tube: Black, smooth SBR rubber compound, resistant to Welding Gases and not suitable for LPG, good resistance to ignition.

Temperature: -25°C to +80°C

Tolerances:

On Inside Diameter: ≤ I.D. 6.3mm: ± 0.55mm. I.D. 6.3 - 10mm: ±0.65mm

Length Tolerance: ± 1%

Important: Welding applications can be hazardous. Please take all the necessary safety precautions.

Part Number	I.D. mm	O.D. mm	W.P. Bar	B.P. Bar	Weight Kg/Mtr	Min. Bend Radius mm
IH30412803 Red Acet	6.3	13.3	20	60	0.15	40
IH30412914 Red Acet	8	15	20	60	0.17	40
IH30412703 Blue Oxy	6.3	13.3	20	60	0.15	40
IH30412915 Blue Oxy	8	15	20	60	0.17	40

BRANCHES AT:

2 Witney Road

Nuffield Industrial Estate

POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

poole@hyphose.com

Unit 3, The Warrior Centre

Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

portsmouth@hyphose.com

Unit 1, Trinity Industrial Estate

Millbrook Road

SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

southampton@hyphose.com

www.hyphose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK