



GAS HOSE - PROPANE

Propane hose manufactured to EN559

Cover: Orange NBR/SBR. Abrasion, oil and weather resistant.

Branding: EN559 / 2 Mpa (20 bar) / size / D H / year.

Reinforcement: High tensile synthetic textile plies.

Tube: Black NBR, resistant to oil products, LPG and propane.

Temperature: -20°C to +70°C

Safety Factor: 3:1 Minimum



I.D.	O.D. mm	W.P. Bar	B.P. Bar	Weight Kg/Mtr
5mm	13	20	60	0.140
1/4"	14	20	60	0.160
5/16"	16	20	60	0.200
3/8"	18	20	60	0.230
1/2"	21	20	60	0.250

BRANCHES AT:

2 Witney Road
Nuffield Industrial Estate

POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

poole@hyphose.com

Unit 3, The Warrior Centre
Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

portsmouth@hyphose.com

Unit 1, Trinity Industrial Estate
Millbrook Road

SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

southampton@hyphose.com

www.hyphose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK