

ISO 7840 FUEL HOSE (WITH CE MARKING)

- To meet the latest European Directive for pleasure craft fitted with inboard engines, flexible fuel lines are required to meet stringent fire testing as part of the ISO Approval.
- Our fuel hose exceeds these requirements as well as conforming to International standards, e.g. USCG, SAE, ABYC, NMMA, etc.
- Manufactured using a 'Barrier Nylon Liner' to prevent fuel permeation even of alcohol blends, it's superior construction and good flexibility make it an ideal choice for engine installations.



Part Number	I.D. mm.	O.D. mm.	Working Pressure psi	Min. Bend Radius in.	Weight kg/m	Type A1/A2
1/4 ISO	6	14	50	2	0.16	A1
5/16 ISO	8	16	50	2.25	0.20	A1
3/8 ISO	10	17	50	2.50	0.23	A1
1/2 ISO	13	21	45	3.00	0.31	A1
5/8 ISO	16	25	45	3.50	0.31	A1
1 1/2 ISO	38	54	36	9.45	1.73	A2
2" ISO	50	66	36	11.81	2.18	A2

Temperature Range:

A1 : -30°C to +140°C

A2 : -20°C to +100°C

for all marine fuels including alcohol blends.

BRANCHES AT:

2 Witney Road

Nuffield Industrial Estate

POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

poole@hyphose.com

Unit 3, The Warrior Centre

Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

portsmouth@hyphose.com

Unit 1, Trinity Industrial Estate

Millbrook Road

SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

southampton@hyphose.com

www.hyphose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK