



LOUISIANA GREEN SUPERELASTIC (LOW TOXIC) – CODE 120



Description: A white spiral helix embedded in a translucent green superelastic flexible PVC.

Temperature Range: -20°C +55°C

Applications: a multi-purpose hose for medium duty suction and discharge use in the agricultural, industrial and aquatics market.

Used In horticultural markets, turf management, in agriculture as seed drill hose, as injector hose and as an irrigation hose.

Also suitable for slurries and dilute chemicals.

Advantages: Lightweight, flexible, transparent smooth bore. Easy to handle, extensive size range. Operates at low temperatures.



I.D. mm.	Weight gr./mtr.	Vacuum m.H2O	Working Pressure bar	Coil Length mtr.
20	275	7	6.5	30
25	330	7	6.5	30
32	460	7	5.5	30
38	550	7	4.5	30
50	810	7	3.5	30
63	1040	7	4.0	50
75	1380	7	3.0	50
102	2160	7	3.0	25
125	3130	5	2.5	25
150	4250	5	2.5	25

**All data refers to performance at 18°C. Any increase of temperature, above or below, will affect the performance data. We reserve the right to change all technical data without prior notice.

BRANCHES AT:

2 Witney Road
Nuffield Industrial Estate

POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

poole@hyphose.com

Unit 3, The Warrior Centre
Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

portsmouth@hyphose.com

Unit 1, Trinity Industrial Estate
Millbrook Road

SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

southampton@hyphose.com

www.hyphose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK