

## LOUISIANA PU (LOW-TOXIC) – CODE 105



**Description:** A white spiral helix embedded in a translucent yellow non-toxic flexible PVC with a translucent anti-abrasive polyurethane liner.

**Temperature Range:** -5°C +60°C

**Applications:** A multi-purpose hose, primarily designed for continuous pneumatic conveyance of pre-mixed plaster from silo to sprayer on building sites.

This hose is also suitable for many other applications such as cement delivery, grain, cereal and other wet or dry abrasive uses.

**Advantages:** Lightweight, flexible, transparent, smooth abrasive resistant liner.

Provides quicker loading and unloading of material, reduces the risk of spillage that causes dust and waste, eliminates use of bags and pallets.

Smooth bore.



I.D. mm.	Wall Thickness mm.	Weight gr./mtr.	Bending Radius mm.	Vacuum m.H2O	Working Pressure bar	Coil Length mtr.
38	3.5	500	200	5.5	5	25
45	3.5	600	240	5.5	4.5	25
50	4	750	260	5.5	4	25

\*\*All data refers to performance at 18°C. Any increase of temperature, above or below, will affect the performance data. We reserve the right to change all technical data without prior notice.

### BRANCHES AT:

2 Witney Road  
Nuffield Industrial Estate

#### POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

[poole@hyphose.com](mailto:poole@hyphose.com)

Unit 3, The Warrior Centre  
Fitzherbert Road, Farlington

#### PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

[portsmouth@hyphose.com](mailto:portsmouth@hyphose.com)

Unit 1, Trinity Industrial Estate  
Millbrook Road

#### SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

[southampton@hyphose.com](mailto:southampton@hyphose.com)

[www.hyphose.com](http://www.hyphose.com)

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK