



## MARINE EXHAUST HOSE



- Lloyds Approved Hose for inboard water-cooled marine diesel exhaust applications in craft up to 24 metres long.
- This very flexible, robust and high quality hose has Lloyds, Rina and DNV type Approval.
- It's construction using top quality material gives it superiority in its application within engine compartments of fishing boats, work boats, pleasure craft etc.
- A very tight bend radius capability aids compact installations and using good quality clamps dispenses with the need to cuff the hoses, thus avoiding damage to the hose end.
- It is also an ideal fuel hose with DNV Approval and can be used with total confidence in marine generator applications.

Lloyds Approval Cert. 99/00027(E1)APP

DNV Approval Cert. S-3597APP

Rina Approval Cert. DIP/4855/03/CS/E/1

### BRANCHES AT:

2 Witney Road

Nuffield Industrial Estate

**POOLE**

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

[poole@hyphose.com](mailto:poole@hyphose.com)

Unit 3, The Warrior Centre

Fitzherbert Road, Farlington

**PORTSMOUTH**

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

[portsmouth@hyphose.com](mailto:portsmouth@hyphose.com)

Unit 1, Trinity Industrial Estate

Millbrook Road

**SOUTHAMPTON**

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

[southampton@hyphose.com](mailto:southampton@hyphose.com)

[www.hyphose.com](http://www.hyphose.com)

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK

**MARINE EXHAUST HOSE**

Part Number	I.D. mm	O.D. mm	Working Pressure psi	Burst Pressure psi	Min. Bend Radius mm	Weight kg/metre
3/4 exhaust	20	30	45	225	60	0.71
1" exhaust	25	35	45	225	75	0.85
1 1/4 exhaust	32	42	45	225	96	1.00
1 3/8 exhaust	35	45	45	225	105	1.08
1 1/2 exhaust	38	48	45	225	114	1.16
1 5/8 exhaust	40	50	45	225	120	1.21
1 3/4 exhaust	45	55	45	225	135	1.34
2" exhaust	51	61	45	225	153	1.49
2 1/4 exhaust	57	67	45	225	171	1.65
2 3/8 exhaust	60	70	45	225	180	1.91
2 1/2 exhaust	63	73	45	225	189	2.00
2 3/4 exhaust	70	80	45	225	210	2.22
3" exhaust	76	86	45	225	228	2.39
3 1/2 exhaust	90	100	45	225	270	2.81
4" exhaust	102	112	45	225	306	3.15
4 1/2 exhaust	115	129	45	225	345	4.11
5" exhaust	127	141	45	225	381	5.02
6" exhaust	152	166	45	225	456	6.23

**Temperature Range:**  
 -30°C to +100°C can also be used for oil suction and delivery.

**BRANCHES AT:**

2 Witney Road Nuffield Industrial Estate <b>POOLE</b> BH17 0GH Tel: 01202 673333 Fax: 01202 687788 <a href="mailto:poole@hyphose.com">poole@hyphose.com</a>	Unit 3, The Warrior Centre Fitzherbert Road, Farlington <b>PORTSMOUTH</b> PO6 1TX Tel: 023 92 324644 Fax: 023 92 325549 <a href="mailto:portsmouth@hyphose.com">portsmouth@hyphose.com</a>	Unit 1, Trinity Industrial Estate Millbrook Road <b>SOUTHAMPTON</b> SO15 0LA Tel: 023 80 512555 Fax: 023 80 512999 <a href="mailto:southampton@hyphose.com">southampton@hyphose.com</a>
---	--	---

**www.hyphose.com**

REGISTERED IN ENGLAND NUMBER 1472439  
 REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH  
 DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK