

MARINE WASTE – CODE 230



Description: A special formulation of PVC compounds which provides excellent resistance to odour permeability. With this kind of PVC plasticizer we obtain a good flexibility at low temperature and a good ageing at high temperatures.

Temperature Range: -10°C +60°C

Applications: For use on toilet wastes on marine craft.

I.D. mm	O.D. mm	Wall Thickness mm.	Weight g/m	Bend Radius mm.	Vacuum m.H2O	Working Pressure bar	Coil Length mtr.
19	25.4	3.2	300	90	7	6	30
25	32.6	3.8	460	110	7	6	30
38	45.6	3.8	670	180	7	5.5	30

**All data refers to performance at 18°C. Any increase of temperature, above or below, will affect the performance data. We reserve the right to change all technical data without prior notice.

BRANCHES AT:

2 Witney Road
Nuffield Industrial Estate

POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

poole@hyphose.com

Unit 3, The Warrior Centre
Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

portsmouth@hyphose.com

Unit 1, Trinity Industrial Estate
Millbrook Road

SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

southampton@hyphose.com

www.hyphose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK