

## OILPRESS N/L 20 - 30



Tube: Smooth, black, oil and fuel resistant NBR rubber compound, suitable for petroleum products with aromatic content not exceeding 50%

Reinforcement: Synthetic textile yarns

Cover: Smooth, black, self-extinguishing, antistatic ( $R < 1 \Omega/m$ ) heat, oil, abrasion and weather resistant CR rubber compound

### Applications:

Suitable for multi-purpose applications requiring transfer of many types of fluids and for petroleum products with aromatic content not exceeding 50%.

The light-weight (L) construction is recommended for light-duty or personalised applications.

### Temperature Range:

-30°C (-22°F) to +100°C (+212°F), with peaks +120° (+248°F)

#### BRANCHES AT:

2 Witney Road  
Nuffield Industrial Estate

#### POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

[poole@hyphose.com](mailto:poole@hyphose.com)

Unit 3, The Warrior Centre  
Fitzherbert Road, Farlington

#### PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

[portsmouth@hyphose.com](mailto:portsmouth@hyphose.com)

Unit 1, Trinity Industrial Estate  
Millbrook Road

#### SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

[southampton@hyphose.com](mailto:southampton@hyphose.com)

[www.hyphose.com](http://www.hyphose.com)

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK