



SMOOTH COVER FUEL HOSE



Tube: Black, oil and fuel resistant, smooth, antistatic (R < 1 MΩ/m), NBR rubber compound

Cover: Black, oil, fuel, abrasion, weather-resistant, smooth, antistatic (R < 1 MΩ/m), NBR/EPDM rubber compound

Reinforcement: Synthetic textile yarns

Applications:

Designed for general applications in fuel systems where low permeability levels are required. Suitable for leaded and unleaded fuels and diesels.

Temperature Range:

-30°C (-22°F) to +100°C (+212°F)

BRANCHES AT:

2 Witney Road
Nuffield Industrial Estate

POOLE

BH17 0GH

Tel: 01202 673333

Fax: 01202 687788

poole@hyphose.com

Unit 3, The Warrior Centre
Fitzherbert Road, Farlington

PORTSMOUTH

PO6 1TX

Tel: 023 92 324644

Fax: 023 92 325549

portsmouth@hyphose.com

Unit 1, Trinity Industrial Estate
Millbrook Road

SOUTHAMPTON

SO15 0LA

Tel: 023 80 512555

Fax: 023 80 512999

southampton@hyphose.com

www.hyphose.com

REGISTERED IN ENGLAND NUMBER 1472439

REGISTERED OFFICE: 2 Witney Road, Nuffield Industrial Estate, POOLE, BH17 0GH

DIRECTORS: S P GRINTER, D W JOHNSON, A-C BARWICK